

AMCM M 4K

Large scale, high productivity system for demanding AM applications.

1 meter building height with up to 4 × 1.2 kW laser power.

Think big.





AMCM M 4K

Benefits

- Compatible with legacy EOS M 400-4 process parameter sets (same focus, beam quality, etc.) (1)
- Large building volume of 450 x 450 x 1,000 mm
- Quattro optical setups available with 400 W, 1 kW or 1.2 kW nLIGHT laser
- Optimized gas flow for larger build volume (Flow Upgrade)
- Powder handling option for semi-automatic (open loop) or full-automatic (closed loop) operation
- · Robust welded machine frame design
- Calibration and overlap adjustment with SmartCAL
- Open software for process optimization
- EOSTATE Exposure OT, Smart Fusion and PowderBed monitoring available
- 1.2 kW AFX nLIGHT laser with beam shaping can be integrated (AMCM M 4K-4 FLX)
- Beam shaping: starting from 85 μm (index 0) Gaus, up to 210 μm (index 6) Ring

Technical Data

AMCM M 4K-4 1kW

AMCM M 4K-4 FLX

Building volume	450 x 450 x 1,000 mm 17.72 x 17.72 x 39.37 in	
Laser type	Yb Fiber laser	
Nominal power	4 x 1 kW	4 x 1.2 kW
Wave length	1,070 nm	
Precision optics	F-theta-lens	
Scanner	high-speed scanner with active cooling	
Scanning speed	up to 7.0 m/s 23 ft./sec	
Focus diameter	approx. 85 μm 0.003 in	approx. 85 – 210 μm 0.003 – 0.008 in
Process gas cooling	gas cooling unit	
Power supply	63 A / 400 V	
Power consumption	20 kW	40 kW
Inert gas supply	7,000 hPa; 20 m³/h 102 psi; 706 ft³/h	
Dimensions with conveyer (W x D x H)	6,340 x 3,450 x 3,900 mm 250 x 136 x 154 in	
Recommended installation space	~90m²	
Weight	approx. 9,300 kg 20,503 lb	
Power supply Power consumption Inert gas supply Dimensions with conveyer (W x D x H)	63 A 20 kW 7,000 hPa; 20 m³/l 6,340 x 3,450 x 3,900	/ 400 V 40 kW h 102 psi; 706 ft³/h mm 250 x 136 x 154 in



Fig 1: AlSi10Mg demo part 1,000 mm height, Ø 380 mm Build time: ~ 73 hours system: AMCM M 4K-1 1kW



Fig 2: CuCrZr demo part. The first ever 1,000 mm CuCrZr AM part. system: AMCM M 4K-1 1kW




Fig 3: Building volume ratio AMCM M 450 and AMCM M 4K.

⁽¹⁾ Processes must all be re-qualified by customer. Consulting for parameter set transfer, e.g. from EOS M 400-x to AMCM M 4K-x on request.